



Hood, Bumper, & Trim Paint

Product Description

VHT® Hood, Bumper, and Trim Paint is a urethane coating formulated with elastomers, which allow for the flexing of paint on pliable surfaces. This unique formula is also well suited for fiberglass, plastic, and other resin based bodywork. Equally suited for metal, VHT Hood, Bumper & Trim Paint offers excellent hide and mar resistance.

Product Characteristics

Color: Black

Finish: Satin

Properties

Product Weight: 6.24 lb/gal

Flash Point: Propellant < 0° F

Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. This system includes surface preparation and Hood, Bumper & Trim Paint.

Prep SP445 Prep Spray

Coat SP27 Black

Uses

Plastic Bumpers, Rubber Bumpers, Body Trim, Kick Panels, Dash Boards, Mirror Castings, ATV Body Work and Motorcycle Body Work.

Surfaces:

- Metal, Plastic, and Resin Based Bodywork.

Application

Caution: For maximum product performance read entire label and directions prior to paint application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. Use grease and wax remover to clean surface. Lightly sand surface with 320-grit sandpaper or Red Scotch Brite pad. Wipe surface down again with grease and wax remover.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16° C) and 95° F (35° C) and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely and 10 seconds after each minute of use. If bare metal is exposed, apply VHT Prime Coat Primer or equivalent first. To spray, hold can parallel 8 to 10 inches from the surface to be painted and use in an even, sweeping motion. Apply two light coats, followed by one medium wet coat.

Apply all coats within 1 hour, allowing 10 minutes between each coat. For all additional coats after one hour, wait 7 days for paint to cure. Dries to touch in 20 minutes, and can be handled in 3 hours. Covers approximately 12-14 square feet.

The EZ TOUCH® Nozzle requires 50% less finger fatigue than a standard nozzle. It allows for greater coverage and less overspray.

Packaging

Fill Weight: 11.25

Per Case: 6 cans

Case Weight: 5.82 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans